



Service with Energy.

HOS SILVERSTAR

240ED Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	240 ft 0 in (73.2 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	14 ft 8 in (4.47 m)
Gross:	1,863 GT	Net :	558 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9273478	O.N.:	1144439	Flag:	U.S.
Certifications:	Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L				
Classifications:	+A1, +AMS, +DPS-2, ACC, American Bureau of Shipping, Loadline, OSV				

PERFORMANCE

Max Speed:	13.0 kts	167 gal/hr (632 l/hr)
Cruise Speed:	10.0 kts	114 gal/hr (431 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	96in (2,438mm)
Primary Generators:	3 x Caterpillar 3406	Total Rating:	960 kW
Bow Thruster:	2 x Brunvoll CPP Tunnel	Total Horsepower:	1,200 hp
Stern Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	600 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	2,762 LT (2,806 MT)	Deck Area:	176ft x 45ft (7,920ft ²) 53.6m x 13.7m (735.8m ²)
Deck Cargo:	1,725 LT (1,753 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	6,240 ft ³ (177 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	8,270 bbl (1,315 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Liquid Mud:	8,270 bbl (1,315 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	30,850 gal (117 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Fuel:	107,650 gal (407 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	317,630 gal (1,202 m ³)	Freezer Area:	850 ft ³ (24 m ³)
Cooler Area:	850 ft ³ (24 m ³)		
Off Ship Firefighting Monitors:	1		
Total Flow Rate:	3,000 gal/min (682 m ³ /hr)		

ELECTRONICS

Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS w/AIS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, L-3 NMS 6000, Mag Compass, MAMS/VMS, Nautronix, Navtex, Public Phone System w/loudhailer, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, Fanbeam

ACCOMMODATIONS

9 air conditioned/heated staterooms certified for 16 person berthing.

SPECIAL FEATURES

Crane: 11t @ 10', Tugger: 1 x 16 St

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.