

HOS WEATHERBY

HOSIAX

HOSMAX280 Offshore Supply Vessel

DIMENSIONS AND REGULATORY INFORMATION

<u>Length:</u> 280 ft 0 in (85.3 m) <u>Beam:</u> 60 ft 0 in (18.3 m) <u>Draft Max:</u> 19 ft 3 in (5.87 m)

Draft Min: 10 ft 3 in (3.12 m)

Gross: 2,998 GT **Net:** 1,101 NT

<u>IMO:</u> 9515840 <u>O.N.:</u> 1210979 <u>Flag:</u> U.S.

Certifications: Oceans-SOLAS, USCG Subchapter L

Classifications: Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, ACP, OSR-C2

PERFORMANCE

Cruise Speed: 10.0 kts 145 gal/hr (549 l/hr) Max Speed: 12.7 kts 290 gal/hr (1,098 l/hr)

PROPULSION, MACHINERY AND STEERING

2 x Caterpillar C280-8 6,598 bhp **Main Engines: Total Horsepower:** CPP, High Efficiency, 4-Blade 106 in (2,692 mm) **Propellers: Propeller Diameter: Primary Generators:** 2 x Caterpillar 3508B 1,820 kW **Total Rating:** 2 x Kato 4,000 kW **Shaft Generators: Total Rating: Aft Bow Thruster:** 1 x Rolls Royce Swing-down Azimuth **Total Rating:** 1,200 hp 1 x Brunvoll CPP Tunnel **Total Rating:** 1,700 hp **Fwd Bow Thruster:** 1 x Brunvoll CPP Tunnel 1,700 hp Stern Thruster: **Total Rating:**

Rudder: High Lift, Independent Steering **Power Generation:** 480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight: 4,723 LT (4,799 MT) **Deck Area:** 201 ft x 50 ft (10,151 ft²)

61.3 m x 15.4 m (943.0 m²)

 Deck Cargo:
 2,700 LT (2,743 MT)
 Deck Load Rating:
 1,200 lbs/ft² (6 MT/m²)

 Dry Bulk:
 12,000 ft³ (340 m³)
 System Pressure:
 80 psi (5.5 bar)

<u>Liquid Mud:</u> 13,322 bbl (2,118 m³) <u>Discharge Rate:</u> 1,100 GPM (250 m³/hr)

Potable Water: 34,820 gal (132 m³)

 Rig Fuel:
 339,357 gal (1,284 m³)
 Discharge Rate:
 1,400 GPM (318 m³/hr)

 Rig Water:
 288,477 gal (1,092 m³)
 Discharge Rate:
 1,400 GPM (318 m³/hr)

Cooler Area: 560 ft³ (16 m³) **Freezer Area:** 525 ft³ (15 m³)

ELECTRONICS

AlS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AlS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, Windbird, X-band Radar

ACCOMMODATIONS

12 air conditioned/heated staterooms certified for 29 person berthing.

SPECIAL FEATURES

Oil Spill Recovery: ABS Capability Class 2 Recovered Oil Capacity: 13,322 bbl (2,118 m³) (>60 °C FP)

Deck Crane:1 x North Pacific MCF-530Max Lift @ Max Radius:1.4 MT @ 30 ftRoll Damping:Anti-Roll Tank, Passive

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

Hornbeck Offshore http://www.hornbeckoffshore.com

Phone: (985)727-2000 Fax: (985)727-3606 Date: 04/30/2024