



# HOS ACHIEVER

## T22 Multi-Purpose Service Vessel



### DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b> 432 ft 1 in (131.7 m)	<b>Beam:</b> 72 ft 1 in (22.0 m)	<b>Draft Max:</b> 22 ft 2 in (6.75 m)
<b>Tonnage/Gross:</b> 8,524 GT	<b>Net :</b> 2,558 NT	<b>Draft Min:</b> 14 ft 0 in (4.27 m)
<b>IMO:</b> 9414163	<b>O.N.:</b> 1759	<b>Flag:</b> Vanuatu
<b>Certifications:</b> Oceans-SOLAS		
<b>Classifications:</b> ABS, A1, AMS, ACCU, DPS-3, HELIDK, HDC 10 t/m <sup>2</sup> , Loadline		

### PERFORMANCE

<b>Cruise Speed:</b> 12.0 kts	296 gal/hr (1,120 l/h)	<b>Max Speed:</b> 13.0 kts
<b>On DP:</b>	146 gal/hr (553 l/h)	

### PROPULSION, MACHINERY AND STEERING

<b>Auxiliary Generators:</b> 2 x MAN B & W 6L 27/38	<b>Total Rating:</b> 3,600 kW
<b>Primary Generators:</b> 4 x MAN B & W 9L 27/38	<b>Total Rating:</b> 11,500 kW
<b>Main Propulsion:</b> 2 x FPP, Steerable Azimuth	<b>Total Horsepower:</b> 8,050 hp
<b>Bow Thrusters:</b> 2 x CPP Tunnel	<b>Total Horsepower:</b> 3,600 hp
<b>Bow Thruster:</b> 1 x CPP Drop Down Azimuth	<b>Total Horsepower:</b> 1,600 hp
	<b>Power Generation:</b> 6.6 kV/60/3 phase

### CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b> 5,096 LT (5,180 MT)	
<b>Ballast Water:</b> 859,250 gal (3,252 m <sup>3</sup> )	
<b>Ship's Fuel:</b> 318,910 gal (1,207 m <sup>3</sup> )	
<b>Potable Water:</b> 145,440 gal (551 m <sup>3</sup> )	
<b>Water Makers:</b> 35,135 gal/day (133 m <sup>3</sup> /day)	
<b>Freezer Area:</b> 3,900 ft <sup>3</sup> (110 m <sup>3</sup> )	<b>Cooler Area:</b> 4,790 ft <sup>3</sup> (136 m <sup>3</sup> )

### ELECTRONICS

Auto Pilot, CCTV Cameras, Depth Sounder, DGPS, EPIRB, Gyro Compass, Joystick Control, Kongsberg SDP 10 DP Sys, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/loudhailer, Radar (S band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X band Radar, CJoy Independent Joystick System, Kongsberg K Pos 21 Dual Redundant DP System, K Pos 11 BU DP 3 Backup DP System

### ACCOMMODATIONS

93 air conditioned/heated staterooms for 267 person(s) berthing total. The rooms are configured as follows:

14 air conditioned staterooms for 1 person(s) berthing each.	17 air conditioned staterooms for 2 person(s) berthing each.
29 air conditioned staterooms for 3 person(s) berthing each.	33 air conditioned staterooms for 4 person(s) berthing each.

Accommodations include:

Multi-Level Fitness Center, Indoor Smoking Lounge, Galley, Coffee & Tea Room, Diner, Internet Cafe/Quiet Room, Laundry Room, Locker/Wash Room, Rec Room, Sick Bay, Deck Changing Room, 3 Conference Rooms, 24 Office Stations

### SPECIAL FEATURES

<b>Helideck Diameter:</b> 73 ft 0 in (22.25 m)	<b>Helideck Rating:</b> Sikorsky S-92, (12 Tons)
<b>Helicopter Equipment:</b> Re-fueling and Restart	
<b>Roll Damping:</b> Active and Passive	<b>Fast Rescue Craft:</b> 1 x 15 Person(s)
<b>Pedestal(Main) Crane:</b> 1 x Huisman Main Hoist Boom	<b>Max Lift @ Max Radius:</b> 50 Mt @ 112 Ft.
	<b>Max Lift @ Min Radius:</b> 160 Mt @ 44 Ft.
	<b>Max Lift @ Max Height:</b> 160 Mt @ 135 Ft abv MD
<b>Pedestal(Aux) Crane:</b> 1 x Huisman Aux Hoist	<b>Max Lift @ Max Radius:</b> 20 Mt @ 146 Ft.
	<b>Max Lift @ Min Radius:</b> 20 Mt @ 26 Ft.
	<b>Max Lift @ Max Height:</b> 20 Mt @ 166 Ft abv MD
<b>Telescopic Gangway:</b> 1 x Uptime Active Motion Compensated Gangway	<b>Operating Length:</b> 19.4m, ±4m
	<b>Operating Angle:</b> +20° / -15°

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.