



HOS BAYOU

310 Multi-Purpose Service Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	302 ft 0 in (92.0 m)	Beam:	64 ft 0 in (19.5 m)	Draft Max:	21 ft 1 in (6.43 m)
Gross:	4,885 GT	Net:	1,465 NT	Draft Min:	12 ft 8 in (3.86 m)
IMO:	9647681	O.N.:	1244577	Flag:	U.S.
Certifications:	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
Classifications:	Loadline, ABS, *DPS-2, FFV-I, (E), *A1, *ACCU, *AMS, OSV, UWILD, ACP, HELIDK, CRC, OSR-C2				

PERFORMANCE

Max Speed:	12.0 kts 208 gal/hr (787 l/hr)
Cruise Speed:	10.0 kts 133 gal/hr (503 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Generators:	4 x Caterpillar 3516C	Total Power:	7,300 kW
Aux. Generator:	2 x Caterpillar C-32	Total Power:	1,880 kW
Propellers:	2 x Schottel Azimuthing Z-Drives	Propeller Diameter:	106 in (2,692 mm)
		Total Horsepower:	6,700 hp
Bow Thruster:	2 x Schottel FPP Tunnel	Total Horsepower:	3,160 hp
		Power Generation:	690V/60/3 phase

CAPACITIES AND DELIVERY RATES

Deadweight:	5,189 LT (5,273 MT)	Deck Area:	145 ft x 55 ft (7,595 ft ²) 44.2 m x 16.8 m (705.6 m ²)
Deck Cargo:	2,075 LT (2,108 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	14,350 ft ³ (406 m ³)	System Pressure:	80 psi (5.5 bar)
Liquid Mud:	20,986 bbl (3,337 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Methanol:	1,960 bbl (312 m ³)	Discharge Rate:	250 GPM (57 m ³ /hr)
Potable Water:	62,549 gal (237 m ³)	Watermaker Cap.:	4,000 USG/day (15 m ³ /day)
Rig Fuel:	268,284 gal (1,015 m ³)	Discharge Rate:	750 GPM (170 m ³ /hr)
Rig Water:	519,162 gal (1,965 m ³)	Discharge Rate:	750 GPM (170 m ³ /hr)
Cooler Cap:	600 ft ³ (17 m ³)	Freezer Cap:	1,000 ft ³ (28 m ³)
Off Ship Firefighting Monitors:	2	Total Flow Rate:	10,586 gal/min (2,406 m ³ /hr)

ELECTRONICS

Auto Pilot, C-NAV, CCTV Cameras, Depth Sounder, Speed Log, DGPS w/AIS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/loudhailer, SARTs, VHF Radio, VHF Radio (Handheld), Anemometer, X-band Radar, S-band Radar AIS, Cyscan, Radascan, DSDL, SSAS, VSAT

ACCOMMODATIONS

24 air conditioned/heated staterooms certified for 70 person(s) berthing.

SPECIAL FEATURES

Helideck Diameter:	73 ft 0 in (22.25 m)	Size Rating:	Sikorsky S-61N
Knuckle Boom Crane:	1 x McGregor Knuckle Boom Crane w/ Active Heave Compensation	Weight Rating:	Sikorsky S-92, (12 Tons)
		Max Lift @ Max Radius:	25 MT @ 105 Ft.
		Max Lift @ Min Radius:	150 MT @ 33 Ft.
		Max Lift @ Max Depth*:	(1-fall) 50 MT @ 9,544 Ft.
		Max Lift @ Max Depth*:	(2-fall) 100 MT @ 4,772 Ft.
		Max Lift @ Max Height:	150 MT @ 125 Ft. abv MD
Deck Crane:	1 x Appleton EB70-53-33	Man Rating:	7.5 MT
		Max Lift @ Max Radius:	3 MT @ 53 Ft.
		Max Lift @ Min Radius:	13 MT @ 16 Ft.
		Man Rating:	0.6 MT
ROV:	2 x Schilling HD 150 HP Work Class	Fast Rescue Craft:	1 x 15 Person(s)
DP Reference:	1 x Kongsberg HiPAP 500	Roll Reduction:	Anti-Roll Tank

* Max water depth will be reduced by the number of wraps required to remain on drum and wire traveling through the system.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck Offshore does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck Offshore accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.