



HOS CROSSFIRE

200 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	190 ft 0 in (57.9 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	13 ft 6 in (4.11 m)
Gross:	1,226 GT	Net:	367 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9203459	O.N.:	1073262	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, +DPS-1, +A1, +AMS				

PERFORMANCE

Cruise Speed:	10.0 kts	70 gal/hr (265 l/hr)	Max Speed:	13.0 kts	150 gal/hr (568 l/hr)
----------------------	----------	----------------------	-------------------	----------	-----------------------

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	FPP, High-Efficiency, 5-Blade	Propeller Diameter:	96 in (2,438 mm)
Primary Generators:	3 x Caterpillar 3406B	Total Rating:	750 kW
Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Rating:	600 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	1,780 LT (1,808 MT)	Deck Area:	140 ft x 46 ft (6,440 ft ²) 42.7 m x 14.0 m (598.3 m ²)
Deck Cargo:	1,385 LT (1,407 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	7,000 ft ³ (198 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	2,714 bbl (431 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Liquid Mud:	2,714 bbl (431 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	54,550 gal (206 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Fuel:	121,840 gal (461 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	208,170 gal (788 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Cooler Area:	400 ft ³ (11 m ³)	Total Flow Rate:	1,250 gal/min (284 m ³ /hr)
Off-ship Firefighting Monitors:	1		

ELECTRONICS

Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Nautronix JSDP 5000, Navtex, Public Phone System w/ loudhailer, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

6 air conditioned/heated staterooms certified for 13 person berthing.

SPECIAL FEATURES

Moonpool, Containerized FIFI Package w/ 5,285 gal/min (1,200m³/hr) Off-ship Firefighting Monitor

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.