



HOS DEEPWATER

240 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	238 ft 0 in (72.5 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	12 ft 10 in (3.91 m)
Gross:	1,549 GT	Net:	464 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9221841	O.N.:	2701341722-7	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, DPS-2, +A1, +AMS, OSR-C2				

PERFORMANCE

Cruise Speed:	10.0 kts	150 gal/hr (568 l/hr)	Max Speed:	12.0 kts	191 gal/hr (723 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	FPP, High-Efficiency, 5-Blade	Propeller Diameter:	96 in (2,438 mm)
Primary Generators:	3 x Caterpillar 3406	Total Rating:	780 kW
Bow Thruster:	2 x Brunvoll CPP Tunnel	Total Rating:	1,200 hp
Stern Thruster:	1 x Brunvoll CPP Tunnel	Total Rating:	250 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	2,259 LT (2,295 MT)	Deck Area:	169 ft x 45 ft (7,670 ft ²) 51.6 m x 13.7 m (712.5 m ²)
Deck Cargo:	1,925 LT (1,956 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	8,400 ft ³ (238 m ³)	System Pressure:	80 psi (5.5 bar)
Liquid Mud:	6,284 bbl (999 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	51,480 gal (195 m ³)		
Recovered Oil (>60 deg C FP):	6,284 bbl (999 m ³)		
Rig Fuel:	132,457 gal (501 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	239,936 gal (908 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Cooler Area:	400 ft ³ (11 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Off-ship Firefighting Monitors:	1	Total Flow Rate:	1,250 gal/min (284 m ³ /hr)

ELECTRONICS

Auto Pilot, C-Nav, Depth Sounder, DGPS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Loudhailer, Mag Compass, MAMS/VMS, Navtex, Public Address system, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, Wartsila CL2 DP

ACCOMMODATIONS

6 air conditioned/heated staterooms certified for 13 person berthing.
Additional deck berthing for 12 person(s).

SPECIAL FEATURES

36" Moonpool

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.