



Service with Energy

HOS DOMINATOR

240E Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	240 ft 0 in (73.2 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	13 ft 0 in (3.96 m)
Gross:	1,848 GT	Net :	554 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9265811	O.N.:	1122403	Flag:	U.S.
Certifications:	Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, OSV				

PERFORMANCE

Max Speed:	12.0 kts	205 gal/hr (776 l/hr)
Cruise Speed:	10.0 kts	164 gal/hr (621 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	95in (2,413mm)
Primary Generators:	3 x Caterpillar 3406B	Total Rating:	750 kW
Bow Thruster:	2 x Brunvoll CPP Tunnel	Total Horsepower:	1,200 hp
Stern Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	600 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	2,054 LT (2,087 MT)	Deck Area:	140ft x 45ft (6,300ft ²) 42.7m x 13.7m (585.3m ²)
Deck Cargo:	1,100 LT (1,118 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	5,600 ft ³ (158 m ³)	System Pressure:	80 psi (5.5 bar)
Potable Water:	112,020 gal (424 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Fuel:	97,440 gal (369 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	461,540 gal (1,747 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Cooler Area:	400 ft ³ (11 m ³)	Total Flow Rate:	3,000 gal/min (682 m ³ /hr)
Off-ship Firefighting Monitors:	1		

ELECTRONICS

Auto Pilot, Beier IVCS 2000, C-Nav, CCTV Cameras, Depth Sounder, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, SARTs, Techsol, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, DGPS w/ AIS, Radar (S-band)

ACCOMMODATIONS

14 air conditioned/heated staterooms certified for 36 person berthing.

Additional deck berthing for 24 person(s)

SPECIAL FEATURES

Deck Crane:	1 x Huisman SMST Telescoping	Max Lift @ Max Radius:	6 MT @ 62 Ft.
		Max Lift @ Min Radius:	24 MT @ 16 Ft.
		Max Lift @ Max Height:	6 MT @ 87 Ft abv MD
Roll Damping:	Anti-Roll Tank		
Moon Pool:	36 in. dia.		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.