



Service with Energy

# HOS PINNACLE

## 250EDF Offshore Supply Vessel



### DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	250 ft 0 in (76.2 m)	<b>Beam:</b>	54 ft 0 in (16.5 m)	<b>Draft Max:</b>	14 ft 10 in (4.52 m)
<b>Gross:</b>	1,955 GT	<b>Net :</b>	586 NT	<b>Draft Min:</b>	8 ft 0 in (2.44 m)
<b>IMO:</b>	9472385	<b>O.N.:</b>	1205149	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, ACC, OSV				

### PERFORMANCE

<b>Max Speed:</b>	14.0 kts    250 gal/hr (946 l/hr)
<b>Cruise Speed:</b>	10.0 kts    90 gal/hr (341 l/hr)

### PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	2 x Caterpillar 3516	<b>Total Horsepower:</b>	6,000 bhp
<b>Propellers:</b>	CPP, High Efficiency, 4-Blade	<b>Propeller Diameter:</b>	106in (2,692mm)
<b>Primary Generators:</b>	3 x Caterpillar C 18	<b>Total Rating:</b>	1,020 kW
<b>Bow Thruster:</b>	2 x Brunvoll CPP Tunnel	<b>Total Horsepower:</b>	1,900 hp
<b>Stern Thruster:</b>	1 x Brunvoll CPP Tunnel	<b>Total Horsepower:</b>	950 hp
<b>Rudder:</b>	Independent Steering, Schilling Fishtail	<b>Power Generation:</b>	480/60/3

### CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	2,707 LT (2,750 MT)	<b>Deck Area:</b>	161ft x 45ft    (7,245ft <sup>2</sup> ) 49.1m x 13.7m    (673.1m <sup>2</sup> )
<b>Deck Cargo:</b>	1,936 LT (1,967 MT)	<b>Deck Load Rating:</b>	1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Dry Bulk:</b>	7,800 ft <sup>3</sup> (221 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Brine:</b>	8,240 bbl (1,310 m <sup>3</sup> )	<b>Discharge Rate:</b>	407 GPM (93 m <sup>3</sup> /hr)
<b>Liquid Mud:</b>	8,240 bbl (1,310 m <sup>3</sup> )	<b>Discharge Rate:</b>	407 GPM (93 m <sup>3</sup> /hr)
<b>Potable Water:</b>	30,850 gal (117 m <sup>3</sup> )	<b>Discharge Rate:</b>	550 GPM (125 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	145,500 gal (551 m <sup>3</sup> )	<b>Discharge Rate:</b>	550 GPM (125 m <sup>3</sup> /hr)
<b>Rig Water:</b>	302,850 gal (1,146 m <sup>3</sup> )	<b>Freezer Area:</b>	400 ft <sup>3</sup> (11 m <sup>3</sup> )
<b>Cooler Area:</b>	400 ft <sup>3</sup> (11 m <sup>3</sup> )	<b>Total Flow Rate:</b>	3,000 gal/min (682 m <sup>3</sup> /hr)
<b>Off-ship Firefighting Monitors:</b>	1		

### ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, L-3 NMS 6000, Mag Compass, MAMS/VMS, Nautronix, Navtex, Public Phone System w/ loudhailer, SARTs, SSAS, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

### ACCOMMODATIONS

11 air conditioned/heated staterooms certified for 24 person berthing.

### SPECIAL FEATURES

10 MT Deck Tugger, Bulk Compressor Air Dryer, Bulk Mud Ventilation Dust Filtering System, Crane: 20t @ 10', Electric Paddle Agitators (LM Tanks #6 & #8 P/S)

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of t equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in wri authorized representative.

103 Northpark Blvd., Suite 300  
Covington, Louisiana 70433  
Rev. 12

**HORNBECK OFFSHORE**  
<http://www.hornbeckoffshore.com>

Phone: (985) 727-2000  
Fax: (985) 727-3606  
Date: 10/20/2016