



Service with Energy.

HOS PIONEER

220 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	220 ft 0 in (67.1 m)	Beam:	46 ft 0 in (14.0 m)	Draft Max:	13 ft 8 in (4.17 m)
Gross:	1,255 GT	Net :	376 NT	Draft Min:	9 ft 0 in (2.74 m)
IMO:	8964434	O.N.:	1091418	Flag:	U.S.
Certifications:	Oceans, SIP, USCG Subchapter L				
Classifications:	American Bureau of Shipping, Loadline				

PERFORMANCE

Max Speed:	12.0 kts	215 gal/hr (814 l/hr)
Cruise Speed:	10.0 kts	120 gal/hr (454 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Cummins QSK60	Total Horsepower:	4,000 hp
Propellers:	FPP, 4-Blade	Propeller Diameter:	96in (2,438mm)
Primary Generators:	2 x Cummins NT855	Total Rating:	250 kW
Bow Thruster:	1 x SMI FPP Tunnel	Total Horsepower:	755 hp
Stern Thruster:	1 x SMI FPP Tunnel	Total Horsepower:	525 hp
Rudder:	Independent Steering, Spade Type	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	1,630 LT (1,656 MT)	Deck Area:	138ft x 38ft (5,244ft ²) 42.1m x 11.6m (487.2m ²)
Deck Cargo:	1,025 LT (1,041 MT)	Deck Load Rating:	540 lbs/ft ² (3 MT/m ²)
Dry Bulk:	8,135 ft ³ (230 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	3,050 bbl (485 m ³)	Discharge Rate:	1,200 GPM (273 m ³ /hr)
Liquid Mud:	3,050 bbl (485 m ³)	Discharge Rate:	1,200 GPM (273 m ³ /hr)
Potable Water:	27,850 gal (105 m ³)	Discharge Rate:	380 GPM (86 m ³ /hr)
Rig Fuel:	112,030 gal (424 m ³)	Discharge Rate:	400 GPM (91 m ³ /hr)
Rig Water:	100,250 gal (379 m ³)	Freezer Area:	375 ft ³ (11 m ³)
Cooler Area:	450 ft ³ (13 m ³)		
Off Ship Firefighting Monitors:	1		
Total Flow Rate:	2,400 gal/min (546 m ³ /hr)		

ELECTRONICS

Auto Pilot, Beier IVCS 2000, C-Nav, CCTV Cameras, Depth Sounder, DGPS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Loudhailer, Mag Compass, MAMS/VMS, Navtex, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

10 air conditioned/heated staterooms certified for 22 person berthing.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.