



HOS SAYLOR

74M Offshore Support Vessel



DIMENSIONS AND REGULATORY INFORMATION

| | | | | | |
|-------------------------|---|--------------|---------------------|-------------------|--------------------|
| Length: | 243 ft 0 in (74.1 m) | Beam: | 54 ft 0 in (16.5 m) | Draft Max: | 20 ft 5in (6.22 m) |
| Gross: | 2,515 GT | Net: | 754 NT | Draft Min: | 8 ft 0 in (2.44 m) |
| IMO: | 9214941 | O.N.: | 8230 | Flag: | Mexico |
| Certifications: | Oceans-SOLAS | | | | |
| Classifications: | Loadline, BV, I (+A1 (E)), +Hull, + Mach (+AMS), Supply Vessel, Unrestricted Navigation, DYNAPOS AM / AT (+DPS-1) | | | | |

PERFORMANCE

| | | | | |
|----------------------|----------|-------------------------|----------------------|----------|
| Max Speed: | 14.0 kts | 327 gal/hr (1,238 l/hr) | Bollard Pull: | 101.3 MT |
| Cruise Speed: | 12.0 kts | 175 gal/hr (662 l/hr) | | |

PROPULSION, MACHINERY AND STEERING

| | | | |
|-----------------------------|------------------------|----------------------------|-----------------|
| Main Engines: | 2 x Wartsila 9L26 | Total Horsepower: | 7,844 hp |
| Propellers: | CPP in Nozzles | Propeller Diameter: | 126in (3,200mm) |
| Shaft Generators: | 2 x Leroy Somer LSA | Total Rating: | 1,600 kW |
| Auxiliary Generator: | 3 x Caterpillar 3412 | Total Rating: | 1,200 kW |
| Bow Thruster: | 1 x Ulstein CPP Tunnel | Total Horsepower: | 770 hp |
| Stern Thruster: | 1 x Ulstein CPP Tunnel | Total Horsepower: | 770 hp |
| Rudder: | High Lift, Ulstein | Power Generation: | 415V/50/3 phase |

CAPACITIES AND DELIVERY RATES

| | | | |
|--|---|--------------------------|--|
| Deadweight: | 3,238 LT (3,292 MT) | Deck Area: | 144 ft 0 in x 46 ft 0 in (6,624 ft ²) 43.9 m x 14.0 m (615.4 m ²) |
| Deck Cargo: | 1,082 LT (1,100 MT) | Deck Load Rating: | 1,106 lbs/ft ² (5.4 MT/m ²) |
| Dry Bulk: | 8,051 ft ³ (228 m ³) | System Pressure: | 80 psi (5.5 bar) |
| Liquid Mud: | 4,071 bbl (647 m ³) | Discharge Rate: | 440 GPM (100 m ³ /hr) |
| Potable Water: | 75,553 gal (286 m ³) | Discharge Rate: | 528 GPM (120 m ³ /hr) |
| Rig Fuel: | 475,325 gal (1,799 m ³) | Discharge Rate: | 528 GPM (120 m ³ /hr) |
| Rig Water: | 233,309 gal (883 m ³) | Freezer Area: | 700 ft ² (20 m ²) |
| Cooler Area: | 700 ft ³ (20 m ³) | Total Flow Rate: | 5,280 GPM (1,200 m ³ /hr) |
| Off Ship Firefighting Monitors: | 2 | | |

ELECTRONICS

GMDSS "A3", Navtex, Single Side Band, VHF Radio, VHF Radio (Handheld), EPIRB, Public Phone System w/loudhailer, Depth Sounder, DGPS w/AIS, Gyro Compass, Mag Compass, SARTs, X-band Radar, Auto Pilot, CCTV Cameras, Joystick Control, MAMS/VMS, Windbird

ACCOMMODATIONS

13 air conditioned/heated staterooms certified for 36 person berthing.

SPECIAL EQUIPMENT

| | | | |
|--------------------|-----------|----------------------|--|
| Shark Jaws: | 200 MT | Tow Pins: | 90.7 MT @ 16 in (406 mm) extension above main deck |
| Tuggers: | 2 x 10 MT | Stern Roller: | 11 ft 4 in x 6 ft 7 in (3.5 m x 2.0 m) |

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck Offshore does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck Offshore accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.