



HOS STRONGLINE

370MPSV Multi-Purpose Service Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	381 ft 4 in (116.2 m)	Beam:	72 ft 0 in (21.9 m)	Draft Max:	19 ft 1 in (5.82 m)
Gross:	5,984 GT	Net:	3,094 NT	Draft Min:	11 ft 6 in (3.51 m)
IMO:	9040534	O.N.:	988333	Flag:	U.S.

Certifications: Oceans-SOLAS, USCG Subchapter D/O, USCG Subchapter I/L

Classifications: Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, FFV 1-NS, OSR-C1, +AMS, ACC, ESP, Oil Carrier/Chemical Carrier/OSV, CRC, ACP

PERFORMANCE

Cruise Speed:	8 kts	190 gal/hr (719 l/hr)	Max Speed:	10 kts	280 gal/hr (1,060 l/hr)
On DP:		105 gal/hr (397 l/hr)	On Standby:		60 gal/hr (227 l/hr)

PROPULSION, MACHINERY AND STEERING

Primary Generators:	4 x Caterpillar 3516C	Total Rating:	8,400 kW
Auxiliary Generators:	3 x Caterpillar C 18	Total Rating:	1,275 kW
Fwd Bow Thruster:	1 x Rolls Royce Marine CPP Tunnel	Total Rating:	1,500 hp
Aft Bow Thruster:	2 x Rolls Royce Marine CPP Drop Down Azimuth	Total Rating:	3,000 hp
Stern Thruster:	1 x Rolls Royce Marine CPP Tunnel	Total Rating:	1,500 hp
Main Propulsion:	2 x Rolls Royce Marine FPP Steerable	Total Rating:	6,000 hp
		Power Generation:	480V/60 Hz/3P, 600V/60 Hz/3P

CAPACITIES AND DELIVERY RATES

Deadweight:	7,869 LT (7,995 MT)	Deck Area:	155 ft x 58 ft (8,875 ft ²)
Deck Cargo:	4,690 LT (4,765 MT)		47.2 m x 17.7 m (824.5 m ²)
Dry Bulk:	6,240 ft ³ (177 m ³)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Brine:	30,961 bbl (4,922 m ³)	System Pressure:	80 psi (5.5 bar)
Cargo Oil (D/O):	24,547 bbl (3,902 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Fresh Water:	64,979 gal (246 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Liquid Mud:	30,961 bbl (4,922 m ³)	Watermaker Cap.:	5,000 USG/day (19 m ³ /day)
Rig Fuel (I/L):	36,274 bbl (5,766 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Rig Water:	32,210 bbl (5,120 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Cooler Area:	850 ft ³ (24 m ³)	Discharge Rate:	750 GPM (170 m ³ /hr)
		Freezer Area:	850 ft ³ (24 m ³)

ELECTRONICS

Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS, EPIRB, Gyro Compass, Joystick Control, Wartsila NMS 6000, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, VSAT

ACCOMMODATIONS

20 air conditioned/heated staterooms for 52 person(s) berthing total. The rooms are configured as follows:

2 air-conditioned staterooms for 1 person(s) berthing each.	10 air-conditioned staterooms for 2 person(s) berthing each.
2 air-conditioned staterooms for 3 person(s) berthing each.	6 air-conditioned staterooms for 4 person(s) berthing each.

Accommodations include: Client Office, Lounge

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 1	Recovered Oil Capacity:	24,547 bbl (3,902 m ³) (<60 °C FP)
Off-ship Firefighting:	ABS FiFi 1	Number of Fire Monitors:	2
		Total Flow Rate:	10,560 gal/min (2,400 m ³ /hr)
Crane:	3 x Hydra Pro HP70/20T	Max Lift @ Max Radius:	2 MT @ 70 ft
		Max Lift @ Min Radius:	20 MT @ 10 ft
Roll Damping:	Anti-Roll Tank, Passive		
Fast Rescue Craft:	1 x 15 Person(s)		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.