



Service with Energy.

HOS SUPER H

200 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	190 ft 0 in (57.9 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	13 ft 6 in (4.11 m)
Gross:	1,226 GT	Net :	367 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9206683	O.N.:	1075422	Flag:	U.S.
Certifications:	Oceans-SOLAS, SIP, USCG Subchapter L				
Classifications:	+A1, +AMS, +DPS-1, American Bureau of Shipping, Loadline				

PERFORMANCE

Max Speed:	13.0 kts	150 gal/hr (568 l/hr)
Cruise Speed:	10.0 kts	70 gal/hr (265 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	FPP, High-Efficiency, 5-Blade	Propeller Diameter:	96in (2,438mm)
Primary Generators:	3 x Caterpillar 3406B	Total Rating:	750 kW
Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	600 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	1,764 LT (1,792 MT)	Deck Area:	140ft x 46ft (6,440ft ²) 42.7m x 14.0m (598.3m ²)
Deck Cargo:	1,385 LT (1,407 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	7,000 ft ³ (198 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	3,590 bbl (571 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Liquid Mud:	3,590 bbl (571 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	54,550 gal (206 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Fuel:	85,050 gal (322 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	208,170 gal (788 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Cooler Area:	400 ft ³ (11 m ³)		
Off Ship Firefighting Monitors:	1		
Total Flow Rate:	1,250 gal/min (284 m ³ /hr)		

ELECTRONICS

Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Loudhailer, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/loudhailer, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), X-band Radar, Nautronix JSDP 5000, Fanbeam, Windbird

ACCOMMODATIONS

6 air conditioned/heated staterooms certified for 12 person berthing.

SPECIAL FEATURES

28" MoonPool

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.