



# HOS SWEET WATER

240EDQ Offshore Supply Vessel



## DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	240 ft 0 in (73.2 m)	<b>Beam:</b>	54 ft 0 in (16.5 m)	<b>Draft Max:</b>	14 ft 10 in (4.52 m)
<b>Gross:</b>	1,934 GT	<b>Net:</b>	580 NT	<b>Draft Min:</b>	8 ft 0 in (2.44 m)
<b>IMO:</b>	9495545	<b>O.N.:</b>	31015892321	<b>Flag:</b>	Mexico
<b>Certifications:</b>	Oceans-SOLAS				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, ACC, OSV, OSR-C2				

## PERFORMANCE

<b>Cruise Speed:</b>	10.0 kts	114 gal/hr (431 l/hr)	<b>Max Speed:</b>	13.0 kts	167 gal/hr (632 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

## PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	2 x Caterpillar 3516C	<b>Total Horsepower:</b>	4,000 hp
<b>Propellers:</b>	CPP, High Efficiency, 4-Blade	<b>Propeller Diameter:</b>	95 in (2,413 mm)
<b>Primary Generators:</b>	3 x Caterpillar C 18	<b>Total Rating:</b>	1,020 kW
<b>Bow Thruster:</b>	2 x Brunvoll CPP Tunnel	<b>Total Rating:</b>	1,900 hp
<b>Stern Thruster:</b>	1 x Brunvoll CPP Tunnel	<b>Total Rating:</b>	950 hp
<b>Rudder:</b>	Independent Steering, Schilling Fishtail	<b>Power Generation:</b>	480V/60 Hz/3-Phase

## CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	2,701 LT (2,744 MT)	<b>Deck Area:</b>	176 ft x 45 ft (7,920 ft <sup>2</sup> ) 53.6 m x 13.7 m (735.8 m <sup>2</sup> )
<b>Deck Cargo:</b>	1,800 LT (1,829 MT)	<b>Deck Load Rating:</b>	1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Dry Bulk:</b>	6,240 ft <sup>3</sup> (177 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Brine:</b>	8,251 bbl (1,312 m <sup>3</sup> )	<b>Discharge Rate:</b>	407 GPM (93 m <sup>3</sup> /hr)
<b>Liquid Mud:</b>	8,251 bbl (1,312 m <sup>3</sup> )	<b>Discharge Rate:</b>	407 GPM (93 m <sup>3</sup> /hr)
<b>Potable Water:</b>	30,850 gal (117 m <sup>3</sup> )		
<b>Recovered Oil (&gt;60 deg C FP):</b>	8,251 bbl (1,312 m <sup>3</sup> )		
<b>Rig Fuel:</b>	107,650 gal (407 m <sup>3</sup> )	<b>Discharge Rate:</b>	550 GPM (125 m <sup>3</sup> /hr)
<b>Rig Water:</b>	317,479 gal (1,202 m <sup>3</sup> )	<b>Discharge Rate:</b>	550 GPM (125 m <sup>3</sup> /hr)
<b>Cooler Area:</b>	850 ft <sup>3</sup> (24 m <sup>3</sup> )	<b>Freezer Area:</b>	850 ft <sup>3</sup> (24 m <sup>3</sup> )
<b>Off-ship Firefighting Monitors:</b>	1	<b>Total Flow Rate:</b>	3,000 gal/min (682 m <sup>3</sup> /hr)

## ELECTRONICS

Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, L-3 NMS 6000, Mag Compass, MAMS/VMS, Public Phone System w/ loudhailer, SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

## ACCOMMODATIONS

11 air conditioned/heated staterooms certified for 24 person berthing.

## SPECIAL FEATURES

<b>Deck Crane:</b>	1 x Hyrda-Pro HP48-20T	<b>Max Lift @ Max Radius:</b>	3 MT @ 48 ft
		<b>Max Lift @ Min Radius:</b>	18 MT @ 10 ft
		<b>Moon Pool:</b>	36 in. dia.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.