



Service with Energy

# HOS THUNDERFOOT

## 200 Offshore Supply Vessel



### DIMENSIONS AND REGULATORY INFORMATION

|                         |  |              |                     |                   |                     |
|-------------------------|--|--------------|---------------------|-------------------|---------------------|
| <b>Length:</b>          | 190 ft 0 in (57.9 m)   | <b>Beam:</b> | 54 ft 0 in (16.5 m) | <b>Draft Max:</b> | 13 ft 6 in (4.11 m) |
| <b>Gross:</b>           | 1,318 GT   | <b>Net :</b> | 395 NT              | <b>Draft Min:</b> | 8 ft 0 in (2.44 m)  |
| <b>IMO:</b>             | 9211937  | <b>O.N.:</b> | 04013741323         | <b>Flag:</b>      | Mexico              |
| <b>Certifications:</b>  | Oceans-SOLAS   |              |                     |                   |                     |
| <b>Classifications:</b> | Loadline, American Bureau of Shipping, +DPS-1, +A1, +AMS, OSR-C2 |              |                     |                   |                     |

### PERFORMANCE

|                      |                                   |
|----------------------|-----------------------------------|
| <b>Max Speed:</b>    | 13.0 kts    150 gal/hr (568 l/hr) |
| <b>Cruise Speed:</b> | 10.0 kts    70 gal/hr (265 l/hr)  |

### PROPULSION, MACHINERY AND STEERING

|                            |  |                            |                    |
|----------------------------|--|----------------------------|--------------------|
| <b>Main Engines:</b>       | 2 x Caterpillar 3516B                    | <b>Total Horsepower:</b>   | 4,000 hp           |
| <b>Propellers:</b>         | FPP, High-Efficiency, 5-Blade            | <b>Propeller Diameter:</b> | 96in (2,438mm)     |
| <b>Primary Generators:</b> | 3 x Caterpillar 3406B                    | <b>Total Rating:</b>       | 750 kW             |
| <b>Bow Thruster:</b>       | 1 x Brunvoll CPP Tunnel                  | <b>Total Horsepower:</b>   | 600 hp             |
| <b>Stern Thruster:</b>     | 1 x SMI FPP Tunnel                       | <b>Total Horsepower:</b>   | 250 hp             |
| <b>Rudder:</b>             | Independent Steering, Schilling Fishtail | <b>Power Generation:</b>   | 480V/60 Hz/3-Phase |

### CAPACITIES AND DELIVERY RATES

|   |   |                          |  |
|---|---|--------------------------|--|
| <b>Deadweight:</b>                      | 1,678 LT (1,705 MT)                         | <b>Deck Area:</b>        | 104ft x 46ft    (4,784ft <sup>2</sup> )<br>31.7m x 14.0m    (444.4m <sup>2</sup> ) |
| <b>Deck Cargo:</b>                      | 1,000 LT (1,016 MT)                         | <b>Deck Load Rating:</b> | 1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )                                   |
| <b>Dry Bulk:</b>                        | 7,000 ft <sup>3</sup> (198 m <sup>3</sup> ) | <b>System Pressure:</b>  | 80 psi (5.5 bar)   |
| <b>Potable Water:</b>                   | 54,562 gal (207 m <sup>3</sup> )            |                          |  |
| <b>Recovered Oil (&gt;60 deg C FP):</b> | 3,590 bbl (571 m <sup>3</sup> )             |                          |  |
| <b>Rig Fuel:</b>                        | 293,501 gal (1,111 m <sup>3</sup> )         | <b>Discharge Rate:</b>   | 550 GPM (125 m <sup>3</sup> /hr)   |
| <b>Rig Water:</b>                       | 148,567 gal (562 m <sup>3</sup> )           | <b>Discharge Rate:</b>   | 550 GPM (125 m <sup>3</sup> /hr)   |
| <b>Cooler Area:</b>                     | 400 ft <sup>3</sup> (11 m <sup>3</sup> )    | <b>Freezer Area:</b>     | 400 ft <sup>3</sup> (11 m <sup>3</sup> )   |
| <b>Off-ship Firefighting Monitors:</b>  | 1   | <b>Total Flow Rate:</b>  | 1,250 gal/min (284 m <sup>3</sup> /hr)   |

### ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Loudhailer, Mag Compass, MAMS/VMS, Nautronix JSDP 5000, Navtex, Public Phone System w/ loudhailer, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

### ACCOMMODATIONS

6 air conditioned/heated staterooms certified for 13 person berthing.  
Additional deck berthing for 12 person(s)

### SPECIAL FEATURES

|                          |                                       |                            |                         |
|--------------------------|---------------------------------------|----------------------------|-------------------------|
| <b>Crane:</b>            | 2 x Hydra Pro 20 Ton Telescoping Boom | <b>Watermaker Cap. :</b>   | 3,000 USG/day           |
| <b>Fenders:</b>          | 4 x Yokohama Fenders per Side         | <b>Personnel Transfer:</b> | Swing Rope Station      |
| <b>Freezer/Chillers:</b> | 2 x 20ft Refrigerated ISO Containers  | <b>Dry Stores:</b>         | 2 x 20ft ISO Containers |
| <b>Tow Hook:</b>         | 100 MT SWL                            |                            |                         |

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.