



HOS CORAL

285 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	285 ft 0 in (86.9 m)	Beam:	64 ft 0 in (19.5 m)	Draft Max:	19 ft 4 in (5.89 m)
Gross:	3,299 GT	Net:	989 NT	Draft Min:	10 ft 0 in (3.05 m)
IMO:	9518622	O.N.:	31015878326	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, FFV 1-NS, +AMS, OSV, OSR-C2				

PERFORMANCE

Cruise Speed:	10.0 kts	212 gal/hr (802 l/hr)	Max Speed:	12.0 kts	297 gal/hr (1,124 l/hr)
On DP:		86 gal/hr (326 l/hr)	On Standby:		12 gal/hr (45 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516C	Total Horsepower:	6,140 bhp
Propellers:	FPP, High-Efficiency, 5-Blade	Propeller Diameter:	112 in (2,845 mm)
Primary Generators:	2 x Caterpillar C 32	Total Rating:	1,420 kW
Bow Thruster:	2 x Berg CPP Tunnel	Total Rating:	2,200 hp
Stern Thruster:	1 x Berg CPP Tunnel	Total Rating:	1,100 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	5,604 LT (5,694 MT)	Deck Area:	204 ft x 54 ft (10,427 ft ²) 62.2 m x 16.5 m (968.7 m ²)
Deck Cargo:	3,000 LT (3,048 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	12,980 ft ³ (367 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	15,212 bbl (2,418 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Liquid Mud:	15,212 bbl (2,418 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Potable Water:	28,444 gal (108 m ³)	Discharge Rate:	800 GPM (182 m ³ /hr)
Rig Fuel:	350,930 gal (1,328 m ³)	Discharge Rate:	800 GPM (182 m ³ /hr)
Rig Water:	591,224 gal (2,238 m ³)	Freezer Area:	460 ft ³ (13 m ³)
Cooler Area:	460 ft ³ (13 m ³)		

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Kongsberg DP, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, SARTs, SSAS, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, Radar (S-band)

ACCOMMODATIONS

13 air conditioned/heated staterooms certified for 24 person berthing.

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	15,212 bbl (2,418 m ³) (>60 °C FP)
Off-ship Firefighting:	FIFI I	Number of Fire Monitors:	2
		Total Flow Rate:	10,560 gal/min (2,400 m ³ /hr)
Deck Crane:	1 x Hydra-Pro HP48-20T	Max Lift @ Max Radius:	3 MT @ 48 ft
		Max Lift @ Min Radius:	18 MT @ 10 ft
Deck Tuggers:	2 x 10 MT		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.