



Service with Energy.

# HOS HAWKE

## 200 Offshore Supply Vessel Well Stimulation



### DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	200 ft 0 in (61.0 m)	<b>Beam:</b>	56 ft 0 in (17.1 m)	<b>Draft Max:</b>	15 ft 0 in (4.57 m)
<b>Gross:</b>	1,489 GT	<b>Net :</b>	446 NT	<b>Draft Min:</b>	9 ft 0 in (2.74 m)
<b>IMO:</b>	9214630	<b>O.N.:</b>	1076185	<b>Flag:</b>	Mexico
<b>Certifications:</b>	Oceans-SOLAS, USCG Subchapter L				
<b>Classifications:</b>	(E), +A1, +AMS, +DPS-1, American Bureau of Shipping, Loadline, OSV, SH-DLA, WS				

### PERFORMANCE

<b>Max Speed:</b>	12.0 kts	150 gal/hr (568 l/hr)
<b>Cruise Speed:</b>	10.0 kts	125 gal/hr (473 l/hr)

### PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	2 x Caterpillar 3516B	<b>Total Horsepower:</b>	4,000 bhp
<b>Propellers:</b>	FPP "Workhorse" Style 5 Blade	<b>Propeller Diameter:</b>	105in (2,667mm)
<b>Primary Generators:</b>	2 x Caterpillar 3306	<b>Total Rating:</b>	340 kW
<b>Auxiliary Generator</b>	2 x Caterpillar 3406	<b>Total Rating:</b>	540 kW
<b>Bow Thruster:</b>	1 x Berg SP CPP Tunnel	<b>Total Horsepower:</b>	1,200 hp
<b>Rudder:</b>	Air-foil, Independent Steering	<b>Power Generation:</b>	480V/60 Hz/3-Phase

### CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	1,767 LT (1,795 MT)	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Acid:</b>	67,300 gal (255 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Potable Water:</b>	32,400 gal (123 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	95,800 gal (363 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Rig Water:</b>	230,400 gal (872 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Xylene:</b>	54,200 gal (205 m <sup>3</sup> )	<b>Freezer Area:</b>	300 ft <sup>3</sup> (8 m <sup>3</sup> )
<b>Cooler Area:</b>	300 ft <sup>3</sup> (8 m <sup>3</sup> )		

### ELECTRONICS

Auto Pilot, C-Nav, Depth Sounder, DGPS w/AIS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Kongsberg SDP 10 DP Sys, Loudhailer, Mag Compass, Navtex, Public Phone System w/loudhailer, Radar, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, HES Satellite Communication Dome

### ACCOMMODATIONS

12 air conditioned/heated staterooms certified for 28 person berthing.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.