



Service with Energy

HOS MYSTIQUE

250EDF Construction Support Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	250 ft 0 in (76.2 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	14 ft 10 in (4.52 m)
Gross:	2,391 GT	Net :	717 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9472323	O.N.:	1205143	Flag:	U.S.
Certifications:	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, ACC, OSV				

PERFORMANCE

Max Speed:	12.0 kts 250 gal/hr (946 l/hr)
Cruise Speed:	10.0 kts 90 gal/hr (341 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516	Total Horsepower:	5,586 bhp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	106in (2,692mm)
Primary Generators:	3 x Caterpillar C 18	Total Rating:	1,020 kW
Auxiliary Generators:	2 x Caterpillar 3412	Total Rating:	1,000 kW
Deck Generators:	1 x Cummins QSK50	Total Rating:	1,250 kW
Bow Thruster:	2 x Brunvoll CPP Tunnel	Total Horsepower:	1,900 hp
Stem Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	950 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	2,333 LT (2,370 MT)	Deck Area:	114ft x 45ft (5,130ft ²) 34.7m x 13.7m (476.6m ²)
Deck Cargo:	1,100 LT (1,118 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	6,240 ft ³ (177 m ³)	System Pressure:	80 psi (5.5 bar)
Potable Water:	30,850 gal (117 m ³)	Watermaker Cap.:	2,000 USG/day (7.57 m ³ /day)
Rig Fuel:	145,900 gal (552 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	321,980 gal (1,219 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Cooler Area:	400 ft ³ (11 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Off-ship Firefighting Monitors:	1	Total Flow Rate:	3,000 gal/min (682 m ³ /hr)

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, L-3 NMS 6000, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, SARTs, SSAS, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

19 air conditioned/heated staterooms certified for 49 person berthing. Accommodations include gym, lounge, and locker room.

SPECIAL FEATURES

Knuckle Boom Crane:	1 x National Oilwell Varco, w/ Active Heave Compensation	Max Lift @ Max Radius:	29 MT @ 95 Ft.
		Max Lift @ Min Radius:	70 MT @ 29 Ft. (1 fall) 100 MT @ 29 Ft. (2 falls)
		Max Lift @ Max Depth:	42.9 MT @ 6,332 Ft. (1,930 m)
		Max Lift @ Max Height:	33 MT @ 110 Ft. abv main deck
Roll Damping:	Anti-Roll Tank (Active Ballast), Bilge Keels	Transducer Well:	22 in. dia.
Hydro-Acoustic:	HIPAP 500 with Deployment System		
ROV:	1 x 150 HP Triton XLS, 1 x 150 HP Schilling HD		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.