



Service with Energy

HOS RIDGEWIND

265WSA Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	260 ft 0 in (79.2 m)	Beam:	60 ft 0 in (18.3 m)	Draft Max:	16 ft 10 in (5.13 m)
Gross:	3,022 GT	Net :	906 NT	Draft Min:	9 ft 0 in (2.74 m)
IMO:	9260706	O.N.:	31016074324	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, ACC, OSV, OSR-C2				

PERFORMANCE

Max Speed:	12.0 kts	138 gal/hr (522 l/hr)
Cruise Speed:	10.0 kts	100 gal/hr (379 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3608	Total Horsepower:	6,780 hp
Shaft Generators:	2 x Main Engine Driven	Total Rating:	4,000 kW
Primary Generators:	2 x Caterpillar 3406	Total Rating:	640 kW
Auxiliary Generators:	2 x Caterpillar 3412	Total Rating:	1,000 kW
	2 x NOV Deck Generators	Total Rating:	2,500 kW
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	118in (2,997mm)
Aft Bow Thruster:	1 x Brunvoll CPP Drop Down Azimuth	Total Horsepower:	1,200 hp
Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	1,200 hp
Stern Thruster:	2 x Brunvoll CPP Tunnel	Total Horsepower:	1,200 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	3,067 LT (3,116 MT)	Deck Area:	123ft x 48ft (5,425ft ²) 37.5m x 14.6m (504m ²)
Deck Cargo:	1,950 LT (1,982 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	10,200 ft ³ (289 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	9,414 bbl (1,497 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Liquid Mud:	9,414 bbl (1,497 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	20,534 gal (78 m ³)	Watermaker Cap.:	8,000 USG/day (30 m ³ /day)
Rig Fuel:	424,408 gal (1,606 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	395,264 gal (1,496 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Cooler Area:	850 ft ³ (24 m ³)	Freezer Area:	850 ft ³ (24 m ³)

ELECTRONICS

Auto Pilot, Beier IVCS 2000, C-Nav, Depth Sounder, DGPS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, Navtex, Public Phone System w/ loudhailer, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, MAMS/VMS, CCTV Cameras

ACCOMMODATIONS

25 air conditioned/heated staterooms certified for 80 person berthing.

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	9,414 bbl (1,497 m ³) (>60 °C FP)
Crane:	National Oilwell Varco, Knuckle Boom w/ Active Heave Compensation	Max Lift @ Radius (Max):	29.2 MT @ 95 ft
		Max Lift @ Radius (Min):	70 MT @ 25 ft (1 fall); 100 MT @ 25 ft (2 falls)
		Max Lift @ Max Depth:	42.7 MT @ 6,562 ft (2,000 m) water depth
		Max Lift @ Max Height:	44 MT @ 114 ft above main deck
Stores Crane:	EBI Telescopic Boom Crane	Lift @ Radius (Max):	2 MT @ 70 ft
		Lift @ Radius (Min):	18 MT @ 10 ft
ROV:	1 x Triton XLX 200 HP Work Class		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.