



Service with Energy

HOS RIDGEWIND

265WSA Multi-Purpose Service Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	260 ft 0 in (79.2 m)	Beam:	60 ft 0 in (18.3 m)	Draft Max:	16 ft 10 in (5.13 m)
Gross:	2,861 GT	Net:	858 NT	Draft Min:	9 ft 0 in (2.74 m)
IMO:	9260706	O.N.:	31016074324	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, ACC, OSV				

PERFORMANCE

Cruise Speed:	10.0 kts	100 gal/hr (379 l/hr)	Max Speed:	12.0 kts	138 gal/hr (522 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3608	Total Horsepower:	6,780 hp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	118 in (2,997 mm)
Shaft Generators:	2 x Main Engine Driven	Total Rating:	4,000 kW
Primary Generators:	2 x Caterpillar 3406	Total Rating:	640 kW
Auxiliary Generators:	2 x Caterpillar 3412	Total Rating:	1,000 kW
Deck Generators:	2 x NOV	Total Rating:	2,500 kW
Aft Bow Thruster:	1 x Brunvoll CPP Drop Down Azimuth	Total Rating:	1,200 hp
Stern Thruster:	2 x Brunvoll CPP Tunnel	Total Rating:	1,200 hp
Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Rating:	1,200 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	3,067 LT (3,116 MT)	Deck Area:	123 ft x 48 ft (5,425 ft ²) 37.5 m x 14.6 m (504.0 m ²)
Deck Cargo:	1,950 LT (1,981 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	10,200 ft ³ (289 m ³)	System Pressure:	80 psi (5.5 bar)
Liquid Mud:	9,414 bbl (1,497 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	20,534 gal (78 m ³)	Watermaker Cap.:	8,000 USG/day (30 m ³ /day)
Rig Fuel:	424,408 gal (1,606 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	395,384 gal (1,497 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Cooler Area:	850 ft ³ (24 m ³)	Freezer Area:	850 ft ³ (24 m ³)

ELECTRONICS

Auto Pilot, Beier IVCS 2000, C-Nav, CCTV Cameras, Depth Sounder, DGPS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

25 air conditioned/heated staterooms for 80 person(s) berthing total. The rooms are configured as follows:

2 air-conditioned staterooms for 1 person(s) berthing each.
16 air-conditioned staterooms for 4 person(s) berthing each.

7 air-conditioned staterooms for 2 person(s) berthing each.

SPECIAL FEATURES

Knuckle Boom Crane:	NOV, Knuckle Boom w/ Active Heave Compensation	Max Lift @ Radius (Max):	40 MT @ 82 ft
		Max Lift @ Radius (Min):	70 MT @ 25 ft (1 fall); 100 MT @ 25 ft (2 falls)
		Max Lift @ Max Depth:	42.7 MT @ 6,562 ft (2,000 m) water depth
		Max Lift @ Max Height:	44 MT @ 114 ft above main deck
Stores Crane:	1 x EBI Telescopic Boom	Max Lift @ Radius (Max):	2 MT @ 70 ft
		Max Lift @ Radius (Min):	18 MT @ 10 ft

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.