



Service with Energy

HOS WINCHESTER

HOSMAX300 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

| | | | | | |
|-------------------------|---|--------------|---------------------|-------------------|---------------------|
| Length: | 292 ft 0 in (89.0 m) | Beam: | 64 ft 0 in (19.5 m) | Draft Max: | 20 ft 0 in (6.10 m) |
| Gross: | 3,764 GT | Net: | 1,266 NT | Draft Min: | 11 ft 3 in (3.43 m) |
| IMO: | 9490064 | O.N.: | 3105891327 | Flag: | Mexico |
| Certifications: | Oceans-SOLAS | | | | |
| Classifications: | Loadline, ABS, +DPS-2, FFV-1, (E), +A1, +AMS, OSV, +ACC, OSR-C2 | | | | |

PERFORMANCE

| | | | |
|----------------------|-----------------------------------|-------------------|-----------------------------------|
| Cruise Speed: | 10.0 kts 140 gal/hr (530 l/hr) | Max Speed: | 12.0 kts 205 gal/hr (776 l/hr) |
|----------------------|-----------------------------------|-------------------|-----------------------------------|

PROPULSION, MACHINERY AND STEERING

| | | | |
|--------------------------|----------------------------------|--------------------------|--------------------|
| Main Engines: | 4 x Cummins QSK60DM | Total Rating: | 7,300 kW |
| Main Propulsion : | 2 x Schottel Azimuthing Z-Drives | Total Rating: | 6,700 hp |
| Bow Thruster: | 2 x Schottel FPP Tunnel | Total Rating: | 3,160 hp |
| | | Power Generation: | 690V/60 Hz/3-Phase |

CAPACITIES AND DELIVERY RATES

| | | | |
|-----------------------|--|--------------------------|---|
| Deadweight: | 5,553 LT (5,642 MT) | Deck Area: | 196 ft x 56 ft (10,930 ft ²) 59.7 m x 17.1 m (1,015.4 m ²) |
| Deck Cargo: | 4,200 LT (4,267 MT) | Deck Load Rating: | 1,024 lbs/ft ² (5 MT/m ²) |
| Dry Bulk: | 14,347 ft ³ (406 m ³) | System Pressure: | 80 psi (5.5 bar) |
| Liquid Mud: | 19,516 bbl (3,102 m ³) | Discharge Rate: | 1,000 GPM (227 m ³ /hr) |
| Methanol: | 1,713 bbl (272 m ³) | Discharge Rate: | 500 GPM (114 m ³ /hr) |
| Potable Water: | 17,190 gal (65 m ³) | Watermaker Cap.: | 2,000 USG/day (7.6 m ³ /day) |
| Rig Fuel: | 254,841 gal (965 m ³) | Discharge Rate: | 750 GPM (170 m ³ /hr) |
| Rig Water: | 547,580 gal (2,073 m ³) | Discharge Rate: | 750 GPM (170 m ³ /hr) |
| Cooler Area: | 500 ft ³ (14 m ³) | Freezer Area: | 375 ft ³ (11 m ³) |

ELECTRONICS

AIS, Anemometer, Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, S-band Radar, SARTs, Speed Log, SSAS, VERIPOS, VHF Radio, VHF Radio (Handheld), VSAT, X-band Radar

ACCOMMODATIONS

14 air conditioned/heated staterooms certified for 31 person berthing.

SPECIAL FEATURES

| | | | |
|-------------------------------|--|---------------------------------|--|
| Oil Spill Recovery: | ABS Capability Class 2 | Recovered Oil Capacity: | 19,516 bbl (3,103 m ³) (>60 °C FP) |
| Off-ship Firefighting: | ABS FIFI 1 | Number of Fire Monitors: | 2 |
| Deck Crane: | 1 x North Pacific MCT-327 | Total Flow Rate: | 10,568 gal/min (2,402 m ³ /hr) |
| | | Max Lift @ Max Radius: | 0.68 MT @ 27 ft |
| | | Max Lift @ Min Radius: | 1.59 MT @ 5 ft |
| Cargo Tank Cleaning: | 2x dual nozzle, dual rotation w/ 110 GPM (25 m ³ /hr) @ 145 psi (10 bar) total each tank | | |

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.